Raw Water Treatment | Industrial | Domestic



Accelerated In-situ Phyco-Remediation of Water Ecosystem


'Towards Low Carbon City'

By: Abdul Latif Osman NUAIM CORPORATION (M) SDN BHD





Phyco-remediation Diatom (bacilla) Fully utilize Ponds & (micro-algae /phytoplankton) Lakes Bio-filters to the waste **F** Photosynthesis (light) (organic and inorganic) Inorganic (Water System) Anoxic O₂ + Organic **Fossil Drains / Rivers** City Ocean **Ponds Ponds** Lakes **Lakes**












How Nano-Technology works?


Formulation of 1-500 nanometers of nutrients (Silica-based)

Avoid Nutrient Pollution Absorb Nutrients & Minerals



Photosynthesis


Oxygenated Water



enhanced **Aerobic**

REDUCE

BOD, COD, TKN 3 Turbidity




Zooplankton, Fish and

other Marine Life.

Better Sludge Digestion. Reduce TSS, TDS, Odour/ Toxicity (<H₂S & NH₃) & Coliform.

Improve

Water Quality, **Increase Aquatic Diversity** & RESTORE NATURAL





Enhancement of DO

Diatom as Powerful Oxygenator (Decomposition Process 'Well-balanced'





Seremban Lake Garden (Nov 2019)




Enhancement of DO


Diatom as Powerful Oxygenator



Dissolved Oxygen in 17 Days at Lake 1



Dissolved Oxygen in 17 Days at Lake 2





Enhancement of DO

Diatom as Powerful Oxygenator

Turbidity (NTU)










Removal of Foul Odor

Replacing the anaerobic process to aerobic





Indah Water Konsortium (IWK) in 2020



Removal of Foul Odor

Replacing the anaerobic process to aerobic

Foul Odor

	Near / Inside Pump House	Aeration Pond	Clarifier Pond	
Pre Treatment	00000	3	60 60	
(11/2/2020)	20 20 20 20 20			
After 8 Days	000000	GP	GD.	
(17/2/2020)	40 40 40 40			
After 15 Days	000000	6		
(27/2/2020)				
After 23 Days	3	- C	6	
(5/3/2020)				
After 30 Days			G	
(11/3/2020)				



Removal of Foul Odor

Replacing the anaerobic process to aerobic

Effluent Compliance

	Effluent (Water Discharged) Parameter							
	BOD (mg/L)	COD (mg/L)	NH3N (mg/L)	NO3 (mg/L)	SS (mg/L)	рН		
Standard A (DOE)	< 20	< 120	< 10	< 20	< 50	6~9		
IWK Data 28-Nov 2019	9	48	16	N/A	16	7		
Pre Treatment (11/2/2020)	31.6	23.0	15.0	NA	N/A	7.6		
After 8 Days (17/2/2020)	23.6	26.0	19.5	NA	N/A	7.71		
After 15 Days (27/2/2020)	4.3	14.9	0.9	4.62	12.0	7.78		
After 23 Days (5/3/2020)	9.9	34.9	11.10	2.62	25.0	6.88		
After 30 Days (11/3/2020)	13.7	39.5	5.27	2.59	28.0	7.08		

Achieved and maintained according to DOE standard (A) in **15 Days** of application.

Electricity Saving


	Aerator 1		Aerator 2		Total kWhr/	Reduction kWhr/	Electrical	Saving
	Run Hrs/Day	kWhr/ Day	Run Hrs/Day	kWhr/ Day	Day	Day	Cost/Year	%
Initial	19	142.5	19	76	218.5		RM27,913	
1 week	14	105	19	76	181	37.5	RM23,123	17%
2 week	4	30	10	40	70	148.5	RM8,943	68%
3 week	4	30	10	40	70	148.5	RM8,943	68%
4 week	19	142.5	19	76	218.5			

Recently, reduce to 90% of Total Operation Time of Aeration System: **2 to 3 hours per day** for both aerators



Rejunavation of Aquatic Life

Diatoms represent a major component at the base of the marine food web, responsible for up to 50% of total oceanic primary production (Mann, 1999).



Increase in fish population in 3 months



Thank You

'Towards Low Carbon City'

By: Abdul Latif Osman (Biotechnologist)

NUAIM CORPORATION (M) SDN BHD

Email: latif@nuaim.net

Phone No: 019 – 221 9630



